

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: **AMAZING HASTE WAX AND GREASE REMOVER**

Recommended Use: Removes wax, grease and tar from metal surfaces, engine cleaner.

Supplier: **TMK Packers Ltd**

Address: 2/20 Trugood Drive, East Tamaki.
PO Box 258 031, Botany, Manukau 2163

Telephone: (+64) 9 273 3753
Facsimile: (+64) 9 273 3752
Website: www.tmkpackers.co.nz
Emergency phone: **National Poisons Centre**
0800 POISON [0800 764 766]



2. HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

HSNO Classifications: 3.1B, 6.1D, 6.3A, 6.4A, 6.8B, 6.9B, 9.1B, 9.3C.

Signal word: **DANGER**



Hazard Statements :

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H320 Causes eye irritation.
H332 Harmful if inhaled.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H402 Harmful to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H433 Harmful to terrestrial vertebrates.

Product: Amazing Haste Wax and Grease Remover
Date of Issue: 29th May, 2015

Page 1 of 9



Prevention Statements :

- P102 Keep out of reach of children.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground container and receiving equipment.
- P241 Use explosion-proof equipment.
- P242 Use non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.
- P260 Do not breathe vapours.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in well-ventilated area.
- P280 Wear protective clothing, gloves and eye protection.
- P281 Use personal protection equipment as required

Response Statements:

- P101 If medical advice is needed, have product container or label at hand.
- P314 Get medical advice if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
P331 Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P312 Call a POISON CENTRE or doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice.
P362 Take off contaminated clothing and wash before re-use.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTRE or doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice.

P370 + P378 In case of fire: Stop leak if safe to do so.

Storage Statements:

- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up

Disposal Statements:

- P501 Dispose of product and containers in accordance with local regulations.



3. COMPOSITION : Information on Ingredients

Chemical Ingredient	CAS No.	Proportion (%)
Naphtha petroleum, light aromatic	64742-95-6	10 - 30
Toluene	108-88-3	10 - 30
Naphtha petroleum, aliphatic	64742-95-6	5 - 15
Naphtha petroleum, light hydrotreated	64742-49-0	5 - 15
Cyclohexane	110-82-7	5 - 15
Methylcyclohexane	108-87-2	5 - 15
n-Hexane	110-54-3	1 - 5

4. FIRST AID MEASURES

For advice, contact the National Poisons Centre (0800 POISON; 0800 764 766) or a doctor.
Have product container or label available.

Swallowed

If swallowed, do NOT induce vomiting. Immediately call a POISON CENTRE or doctor for advice. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs.

Skin Contact

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with soap and water. If irritation persists, get medical attention.

Eye Contact

Hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes. Remove contact lenses if present and easy to do after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.

Inhalation

Move the victim to fresh air immediately. Keep warm and at rest until recovered. Get medical attention if symptoms continue.
Begin artificial respiration if breathing has stopped and get immediate medical attention.

First Aid facilities

Provide eye baths and safety showers close to areas where splashing may occur.

Medical Attention

Treat according to symptoms. Risk of aspiration to lungs with potential to cause chemical pneumonitis. Gastric lavage should only be undertaken after endotracheal intubation.

5. FIRE FIGHTING MEASURES

Flashpoint: 4°C (toluene)

Flammable limits: LFL :not available UFL: not available

Extinguishing media:

Dry chemical or alcohol foam. Do not use water jet. Use fine water spray or water fog on large fires only.

Fire & Explosion hazards:

Liquid and vapours are highly flammable. Vapour is heavier than air, spreads along the ground and distant



ignition is possible. Do not breathe smoke, gases or vapours generated in a fire. Expansion or decomposition of containers may lead to rupture of containers.

Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus (SCBA).

In event of fire:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus and protective gloves.
- Shut off product that may 'fuel' a fire if safe to do so.
- If safe, switch off electrical equipment until vapour hazard removed.
- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet.
- Prevent product and extinguishing media from escaping to drains and waterways.

Hazards from combustion products: Carbon dioxide, carbon monoxide.

Hazchem Code: 3YE

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures & Containment:

Refer to "Fire Fighting Measures", "First Aid Measures" and "Stability and Reactivity".

Minor spills

- Remove or eliminate all ignition sources.
- Clean up spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Collect residues and waste material in a labeled container suitable for flammables.
- Seal container and dispose of safely.

Major spills

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or low-lying areas.
- Eliminate sources of ignition, naked lights. No smoking.
- Increase ventilation.
- Water spray or fog may be used to disperse/absorb vapour.
- Use only spark-proof tools, e.g. shovels, and explosion proof equipment, e.g. pumps.
- Collect recoverable product into labeled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.



7. HANDLING AND STORAGE

Precautions for safe handling:

Read product label before use. This product is highly flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static discharge. Use grounding leads to avoid discharge (electrical spark) spark-free tools and equipment suitable for flammables. Do not use plastic buckets. Use outdoors or in well-ventilated area. Wear personal protective equipment. Wash hands with soap and water after handling. Wash protective clothing separate to household laundry.

Conditions for safe storage:

Keep out of reach of children. Store locked up in a cool, dry place away from direct sunlight. This product will fuel a fire in progress. Check containers periodically for leaks or distortion.

Incompatible materials:

Natural rubber, butyl rubber, nitrile rubber, EDPM, polystyrene.

8. EXPOSURE CONTROLS : PERSONAL PROTECTION

Health Exposure Standards:

Workplace Exposure Standards (WES) has been set for components in this product.

	WES-TWA	WES-STEL
Cyclohexane	100 ppm (350 mg/m ³)	300 ppm (1050 mg/m ³)
n-Hexane _{BIO}	20 ppm (72 mg/m ³)	-
Methylcyclohexane	400 ppm (1610 mg/m ³)	-
Toluene _{SKIN}	50 ppm (188 mg/m ³)	-

Biological limit values:

N-Hexane end of shift; 5 mg/L 2,5-hexandione in urine

Engineering Controls:

Ventilation:

Do not breathe vapours. Use product outdoors or in well-ventilated area. The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in confined spaces. Use explosion-proof ventilation equipment. Use personal protective respiratory equipment if concentrations in air are unknown, or meet or exceed Health Exposure Limits.

Personal Protective Equipment:

Respiratory Protection: It is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product. Where concentrations in air may exceed the limits described in the Workplace Exposure Standards, use an appropriate positive pressure breathing apparatus.

Eye Protection: Protect eyes from splashes or vapour. It is recommended safety glasses with side shields or chemical goggles be worn depending on circumstances of use.

Skin/ Body Protection:

Wear chemical resistant gloves if any risk of contact with liquid. It is also recommended to wear long sleeves and long trousers or coveralls, and chemical resistant shoes or boots.



9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear colourless liquid
Odour	-	Solvent
Flash Point	°C	4 (toluene)
Boiling Point	°C	Not determined
Specific gravity @ 20°C	g/ml	0.78 – 0.81
Vapour Pressure @ 20°C	kPa	Not available
Vapour Density @ 20°C	kPa	Not available
Explosive Limits in Air	%	Not available
Alkalinity/acidity (as pH)	-	Not applicable
Solubility in Water	kg/m ³	Immiscible

The values listed are indicative of this product's physical and chemical properties.

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at room temperature and pressure.
Conditions to avoid:	Sources of heat and ignition, open flames.
Hazardous decomposition products:	No decomposition products except on burning. See "Fire Fighting Measures" and "Hazardous Reactions".
Hazardous reactions:	Oxidizing agents.
Hazardous polymerization:	Not known to occur.

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

Harmful if swallowed. Will irritate throat and tube to stomach. Symptoms of ingestion may also include headaches, nausea and dizziness. Aspiration into the lungs by ingestion or vomiting may result in chemical pneumonitis in pulmonary odema.

Eye Contact

Irritating to eyes with possible symptoms of tearing, redness and maybe swelling.

Skin Contact

Harmful and irritating to skin. Prolonged or repeated exposure may cause dermatitis and will increase risk of dryness and cracking of skin.

Inhalation

Harmful by inhalation. Vapour may be irritating to nose and throat. Symptoms may include coughing, wheezing, difficulty breathing, drowsiness and dizziness. Exposure to high concentrations over an extended time may result in adverse central nervous system effects (nausea, headaches, loss of consciousness, coma and death).

Chronic Effects

Prolonged contact with product will result in irritant contact dermatitis. Any existing dermatitis may be aggravated. Reaped or prolonged exposure to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys.



Other Health Effects Information:

Toluene is suspected of causing adverse effects to fertility or reproductive development.

Toxicological Information:

Cyclohexane	Oral, LD ₅₀ ,mouse 813 mg/kg Inhalation, LC ₅₀ (4 h), rat 13.9 mg/L
Methylcyclohexane	Oral, LD ₅₀ ,mouse 2250 mg/kg
Toluene	Oral, LD ₅₀ ,rat 636mg/kg Dermal, LD ₅₀ , rabbit > 2000 mg/kg Inhalation, LC ₅₀ (4 h), rat 12.5 mg/L

12. ECOLOGICAL INFORMATION

Do not discharge product to sewer, drains or waterways.

Ecotoxicity:

Aquatic toxicity: Product is classified as being toxic to aquatic life with long-lasting effects.

Ecotoxicity Information: Not available

Persistence/degradability: Is not expected to bioaccumulate significantly. Product is expected to biodegrade although some components are not readily biodegradable.

Mobility: Not miscible in water. Product floats on water. Evaporates rapidly. If product enters soil, it will be mobile and may contaminate ground-water.

Other information: Product is harmful to terrestrial vertebrates.

Environmental Exposure Standards: Not set.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry. If not recycled, puncture and crush before disposal to landfill. Do not use container for storage of other products.

14. TRANSPORT INFORMATION

UN Number:	1993
Shipping name:	FLAMMABLE LIQUID (CONTAINS PETROLEUM HYDROCARBONS)
Class:	3
Packing group:	II
Hazchem code:	3YE

Product: Amazing Haste Wax and Grease Remover

Date of Issue: 29th May, 2015

Page 7 of 9



Dangerous Goods Segregation

This product is classified as Dangerous Goods Class 3, Packing Group II.
Please consult NZS 5433:2012 Transport of Dangerous Goods on Land for information.



15. REGULATORY INFORMATION

Country/ Region: New Zealand
Inventory: NZ Inventory of Chemicals
Status: Listed

EPA New Zealand HSNO Approval Code: HSR 002650; Solvent (Flammable) Group Standard 2006.
Refer www.epa.govt.nz for information on Controls.

16. OTHER INFORMATION

Issue: 4
Date of Issue: 20th May, 2015
Reasons for Issue: 5-year review of Safety Data Sheet.
Replaces: 27th April 2010

Abbreviations:

CAS No Chemical Abstracts Number
EPA Environmental Risk Management Authority
HSNO Hazardous Substances and New Organisms
NZIoC New Zealand Inventory of Chemicals
STEL Short Term Exposure Limit
TWA Time Weighted Average
WES Workplace Exposure Standard

References:

Supplier Safety Data Sheets
EPA website: www.epa.govt.nz

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact TMK Packers Ltd.

END OF SAFETY DATA SHEET



