

www.tmkpackers.co.nz

2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EPOXY THINNER

Recommended Use: Paint Thinner

Supplier: TMK Packers Ltd

Address: 2/20 Trugood Drive, East Tamaki.

PO Box 258 031, Botany, Manukau 2163

Telephone: (+64) 9 273 3753 Facsimile: (+64) 9 273 3752 Website: www.tmkpackers.co.nz

Emergency phone: TMK Packers Ltd

0800 273 327

2. HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

HSNO Classifications: 3.1B, 6.1D(Inhalation), 6.3B, 6.4A, 6.9B, 9.1B

Signal word: DANGER







Hazard Statements:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H433 Harmful to terrestrial vertebrates.

Product: Epoxy Thinner

Date of Issue: 30th November 2023, Version 1 Page 1 of 8





www.tmkpackers.co.nz

2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Prevention Statements:

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground container and receiving equipment.

P241 Use explosion-proof equipment.

P242 Use non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P260 Do not breathe vapours.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use only outdoors or in well-ventilated areas.

P280 Wear protective clothing, gloves, and eye

protection.P281 Use personal protection equipment as

required

Response Statements:

P101 If medical advice is needed, have product container or label at hand.

P314 Get medical advice if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice.

P301 + P312 IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a POISON CENTRE or doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice.

P362 Take off contaminated clothing and wash before re-use.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTRE or doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P370 + P378 in case of fire: Stop leak if safe to do so.

Storage Statements:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up

Disposal Statements:

P501 Dispose of product and containers in accordance with local regulations.

3. COMPOSITION: Information on Ingredients

or corn collision in an englishment			
Chemical Ingredient	CAS No.	Proportion (%)	
Methyl Ethyl Ketone	78-93-3	<60	
Xylene	1330-20-7	<50	
Isopropyl Alcohol	67-63-0	<60	

Product: Epoxy Thinner

Date of Issue: 30th November 2023, Version 1



Page 2 of 8



www.tmkpackers.co.nz

East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

2/20 Trugood Drive

4. FIRST AID MEASURES

For advice, contact the National Poisons Centre (0800 POISON; 0800 764 766) or a doctor. Have product container or label available.

Swallowed

If swallowed, do NOT induce vomiting. Rinse mouth. If a person feels unwell get medical advice. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs.

Skin Contact

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with soap and water. If irritation persists, get medical attention.

Eye Contact

Hold eyelids apart and flush the eye continuously with running water. Continue flushing. for at least 15 minutes. Remove contact lenses if present and easy to do after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.

Inhalation

Move the victim to fresh air immediately. Keep warm and rest until recover. Get medical attention is symptoms continue.

Begin artificial respiration if breathing has stopped and get immediate medical attention.

First Aid facilities

Provide eye baths and safety showers close to areas where splashing may occur.

Medical Attention

Treat according to symptoms. Risk of aspiration to lungs. Gastric lavage should only be undertaken after endotracheal intubation.

5. FIRE FIGHTING MEASURES

Flashpoint: 24°C (typical)

Flammable limits: LFL: 1.2% UFL: 8.0%

Extinguishing media:

Dry chemical, alcohol foam or carbon dioxide. Do not use water jet.

Fire & Explosion hazards:

Liquid and vapours are highly flammable. Vapour is heavier than air, spreads along the ground and distant ignition is possible. Do not breathe smoke, gases or vapours generated in a fire. Expansion or decomposition of containers may lead to rupture of containers.

Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus (SCBA).

In event of fire:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus and protective gloves.
- Shut off product that may 'fuel' a fire if safe to do so.
- If safe, switch off electrical equipment until vapour hazard removed.

Product: Epoxy Thinner

Date of Issue: 30th November 2023, Version 1 Page 3 of 8





Tel (09) 273 3753 Fax (09) 273 3752 Tel 0800 27 33 27 Fax 0800 27 33 26 sales@tmkpackers.co.nz www.tmkpackers.co.nz

2/20 Trugood Drive **East Tamaki Auckland** PO Box 258 031 **Botany** Manukau 2163

- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet.
- Prevent product and extinguishing media from escaping to drains and waterways.

Hazards from combustion products: Carbon dioxide, carbon monoxide

Hazchem Code: 3(Y)E

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures & Containment:

Refer to "Fire Fighting Measures", "First Aid Measures" and "Stability and Reactivity".

Minor spills

- Remove or eliminate all ignition sources.
- Clean up spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Collect residues and waste material in a labeled container suitable for flammables.
- Seal container and dispose of it safely.

Major spills

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Stop leaking if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or low-lying
- Eliminate sources of ignition, naked lights. No smoking.
- Increase ventilation.
- Water spray or fog may be used to disperse/absorb vapour.
- Use only spark-proof tools, e.g. shovels, and explosion-proof equipment, e.g. pumps.
- Collect recoverable products into labeled contains for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.

7. HANDLING AND STORAGE

Precautions for safe handling:

Read product label before use. Approved Handler required. This product is highly flammable. Do not open near open flame, sources of heat or ignition. No smoking, Keep container closed, Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static discharge. Use grounding leads to avoid discharge (electrical spark) spark-free tools and equipment suitable for flammables. Do not use plastic buckets. Use outdoors or in well-ventilated area. Wear personal protective equipment. Wash hands with soap and water after handling. Wash protective clothing separate to household laundry.

Product: **Epoxy Thinner**

30th November 2023, Version 1 Date of Issue:





Tel (09) 273 3753 Fax (09) 273 3752 Tel 0800 27 33 27 Fax 0800 27 33 26 sales@tmkpackers.co.nz www.tmkpackers.co.nz

2/20 Trugood Drive **East Tamaki Auckland** PO Box 258 031 **Botany** Manukau 2163

Conditions for safe storage:

Keep out of reach of children. Store in a cool, dry place away from direct sunlight. This product will fuel a fire in progress. Check containers periodically for leaks or distortion.

Incompatible materials:

Natural rubber, butyl rubber, EDPM, polystyrene.

8. EXPOSURE CONTROLS: PERSONAL PROTECTION

Biological limit values:

None established.

Engineering Controls:

Ventilation:

Do not breathe vapours. Use product outdoors or in well-ventilated area. The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in confined spaces. Use explosion-proof ventilation equipment. Use personal protective respiratory equipment if concentrations in air are unknown or meet or exceed Health Exposure Limits.

Personal Protective Equipment:

Respiratory Protection: It is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product. Where concentrations in air may exceed the limits described in the Workplace Exposure Standards, use an appropriate positive pressure breathing apparatus.

Eye Protection: Protect eyes from splashes or vapour. It is recommended safety glasses with side shields or chemical goggles be worn depending on circumstances of use.

Skin/ Body Protection:

Wear chemical resistant gloves if any risk of contact with liquid. It is also recommended to wear long sleeves and long trousers or coveralls, and chemical resistant shoes or boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear colourless liquid
Odour	-	Solvent odour
Flash Point	0C	24
% Volatiles	-	100
Specific gravity @ 20°C	g/ml	0.80
Vapour Pressure @ 20°C	kPa	Not Available
Vapour Density @ 20°C	kPa	3.0
Evaporation Rate	-	Not Available
Alkalinity/acidity (as pH)	-	Not applicable
Solubility in Water	kg/m³	Partly soluble

The values listed are indicative of this product's physical and chemical properties.

Product: **Epoxy Thinner**

30th November 2023, Version 1 Date of Issue:





www.tmkpackers.co.nz

2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature and pressure.

Conditions to avoid: Sources of heat and ignition, open flames.

Hazardous decomposition products: No decomposition products except on burning.

See "Fire Fighting Measures" and "Hazardous Reactions".

Hazardous reactions: Oxidizing agents, mineral acids, halogenated organic compounds and

peroxides. In combination with ethyl alcohol will increase the risk of adverse

health effects.

Hazardous polymerization: Not known to occur.

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

Harmful if swallowed. Will irritate throat and tube to stomach. May cause nausea. Aspiration into the lungs by ingestion or vomiting may result in chemical pneumonitis.

Eye Contact

Irritating to eyes with possible symptoms of redness, swelling, burning sensation and blurred vision.

Skin Contact

Harmful and irritating to skin. Prolonged or repeated exposure may cause dermatitis and will increase risk of dryness and cracking of skin.

Inhalation

Harmful by inhalation. Vapour may be irritating to nose and throat. Exposure to high concentrations over an extended time will result in dizziness and drowsiness and other adverse central nervous system effects (nausea, headaches, loss of consciousness, coma and death).

Chronic Effects

Repeated over-exposure may cause hemolysis of the red blood cells leading to possible liver and kidney damage. There is evidence of potentially irreversible damage to the peripheral nervous system, particularly arms and legs. Prolonged contact with product will result in irritant contact dermatitis. Any existing dermatitis may be aggravated.

Other Health Effects Information:

Toluene is suspected of causing adverse effects to fertility or reproductive development.

Product: Epoxy Thinner

Date of Issue: 30th November 2023, Version 1 Page 6 of 8





www.tmkpackers.co.nz

2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity: Product is classified as being harmful to aquatic life with long-lasting.

effects.

Ecotoxicity Information: Not available

Persistence/degradability: Does not bioaccumulate significantly. Product is expected to rapidly.

biodegrade.

Mobility: Product floats on water. Evaporates rapidly. If product enters soil, it will

be mobile and may contaminate groundwater.

Other information: None

Environmental Exposure Standards: Not set.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain vapours that are flammable. Ensure that empty packaging is allowed to dry. If not recycled, puncture and crush before disposal to landfill. Do not use containers for storage of other products.

14. TRANSPORT INFORMATION

UN Number: 1307

Shipping name: Flammable Liquid N.O.S

Class: 3
Packing group: III
Hazchem code: 3YE

Dangerous Goods Segregation

This product is classified as Dangerous Goods Class 3, Packing Group II.

Please consult NZS 5433:2012 Transport of Dangerous Goods on Land for information.





Product: Epoxy Thinner

Date of Issue: 30th November 2023, Version 1

Page 7 of 8





Tel (09) 273 3753 Fax (09) 273 3752 Tel 0800 27 33 27 Fax 0800 27 33 26

sales@tmkpackers.co.nz www.tmkpackers.co.nz

2/20 Trugood Drive **East Tamaki Auckland** PO Box 258 031 **Botany** Manukau 2163

15. REGULATORY INFORMATION

Country/ Region: New Zealand

Inventory: NZ Inventory of Chemicals

Status: Listed

EPA New Zealand HSNO Approval Code: HSR002662 Refer www.epa.govt.nz for information on Controls.

Approved Handler control applies.

16. OTHER INFORMATION

Issue:

Date of Issue: 30th November 2023

Reasons for Issue: **New SDS**

Replaces:

Abbreviations:

CAS No Chemical Abstracts Number

EPA Environmental Risk Management Authority HSNO Hazardous Substances and New Organisms

NZIoC New Zealand Inventory of Chemicals

Short Term Exposure Limit STEL Time Weighted Average TWA **WES** Workplace Exposure Standard

References:

Supplier Safety Data Sheets EPA website: www.epa.govt.nz

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact TMK Packers Ltd.

END OF SAFETY DATA SHEET

Product: **Epoxy Thinner**

Date of Issue: 30th November 2023, Version 1

