

2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: ISOPAR H

Recommended Use: Industrial Solvent

Supplier: TMK Packers Ltd

Address: 2/20 Trugood Drive, East Tamaki.

PO Box 258 031, Botany, Manukau 2163

 Telephone:
 (+64) 9 273 3753

 Facsimile:
 (+64) 9 273 3752

 Website:
 www.tmkpackers.co.nz

Emergency phone: National Poisons Centre

0800 POISON [0800 764 766]

2. HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

HSNO Classifications: 3.1C, 6.1E, 6.3B





Signal word: DANGER

Hazard Statements:

H226 Flammable liquid and vapour

H304 Harmful if swallowed and enters airways H316 Causes mild

skin irritation

Prevention Statements:

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed

P240 Ground container and receiving equipment

P241 Use explosion-proof electrical, ventilating and lighting equipment P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P280 Wear protective gloves, protective clothing and eye protection

Product: ISOPAR H Date of Issue: 13th April 2023

Page 1 of 8





2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Response Statements:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor. P331 Do NOT induce vomiting

P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P332 + P313 If skin irritation occurs: Get medical advice.

P370 + P378 In case of fire: Stop leak if safe to do so.

Storage Statements:

P403 + P235 Store in a well-ventilated.

P405 Store locked up.

Disposal Statement:

P501 Dispose of product and containers in accordance with local regulations.

3. COMPOSITION: Information on Ingredients

Chemical Ingredient	CAS No.	Proportion (%)
Naphtha (petroleum) hydrotreated heavy	64742-48-9	100

4. FIRST AID MEASURES

For advice, contact National Poisons Centre (0800 POISON; 0800 764 766) or a doctor. Have product container or label available. Get medical advice if you feel unwell.

Swallowed

If swallowed, do NOT induce vomiting. Rinse mouth. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.

Product: ISOPAR H
Date of Issue: 13th April 202





2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Skin Contact

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, get medical attention.

Eye Contact

Hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes. Remove contact lenses if present and easy to do, after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.

Inhalation

Move the victim to fresh air immediately. Keep warm and at rest until recovered. Get medical attention if symptoms continue. Begin artificial respiration if breathing has stopped. Get immediate medical attention.

First Aid facilities

Provide eye baths and safety showers close to areas where splashing may occur.

Advice to doctor

Treat according to symptoms. Gastric lavage may be indicated if ingested. Risk of aspiration into lungs with potential to cause chemical pneumonitis.

5. FIRE FIGHTING MEASURES

Flashpoint: 49°C

Flammable limits: LFL: not available UFL: not available **Extinguishing media:** Dry chemical or alcohol foam or CO₂.

Fire & Explosion hazards:

Liquid and vapours are highly flammable. Do not breathe smoke, gases or vapours generated in a fire. Expansion or decomposition of containers may lead to rupture of containers.

Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus (SCBA).

In event of fire:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus and protective gloves.
- Shut off product that may 'fuel' a fire if safe to do so.
- If safe, switch off electrical equipment until vapour hazard removed.
- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet
- Prevent product and extinguishing media from escaping to drains and waterways.

Hazards from combustion products: Carbon dioxide, carbon monoxide, incomplete combustion products, smoke, fume.

Hazchem Code: 3YE

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures & Containment:

Refer to "Fire Fighting Measures", "First Aid Measures" and "Stability and Reactivity".

Product: ISOPAR H Date of Issue: 13th April 2023

Page 3 of 8





2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Minor spills

- Remove or eliminate all ignition sources.
- Clean up spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantifies with vermiculite or other absorbent material.
- Collect residues and waste material in a labeled container suitable for flammables.
- · Seal container and dispose of safely.

Major spills

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or low-lying areas.
- Eliminate sources of ignition, naked lights. No smoking.
- Increase ventilation.
- Water spray or fog may be used to disperse/absorb vapour.
- Use only spark-proof tools, e.g. shovels, and explosion proof equipment, e.g. pumps.
- Collect recoverable product into labeled contains for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- · Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.

7. HANDLING AND STORAGE

Precautions for safe handling:

Read product label before use. This product is highly flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static discharge.

Use outdoors or in well-ventilated area. Wear personal protective equipment. Wash hands with soap and water after handling. Wash protective clothing separate to household laundry.

Conditions for safe storage:

Keep out of reach of children. Store locked up in a cool, dry place away from direct sunlight. This product will fuel a fire in progress. Check containers periodically for leaks or distortion.

Incompatible materials: Natural rubber, butyl rubber, EDPM, polystyrene.

8. EXPOSURE CONTROLS: PERSONAL PROTECTION

Health Exposure Standards:

No Workplace Exposure Standard (WES) has been set by the Occupational Safety and Health Service specifically for this substance:

Supplier recommendation for product: RCP -TWA 177 ppm (1200 mg/m³)

Product: ISOPAR H Date of Issue: 13th April 2023

Page 4 of 8





2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Biological limit values: None established.

Engineering Controls:

Ventilation:

Use product outdoors or in well-ventilated area. If using product in commercial or industrial situations where concentrations in air may exceed the limits described in the Workplace Exposure Standards The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in confined spaces. Use explosion-proof ventilation equipment.

Personal Protective Equipment:

Respiratory Protection: When using product in commercial or industrial situations where concentrations in air may exceed the limits described in the Workplace Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

Eye Protection: Protect eyes from splashes, aerosols or vapour. It is recommended safety glasses with side shields or goggles be worn where there is risk of splashes.

Skin/ Body Protection:

If using product in commercial or industrial situations, wear chemical resistant gloves, e.g. PVC, nitrile rubber, also safety footwear or safety gumboots, e.g. rubber. Always wear long sleeves and long trousers or coveralls.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear colourless liquid
Boiling Point/Range	°C	171 - 191
Flash Point	°C	49 °C
Specific gravity @ 20°C	g/ml	0.759
Vapour Pressure @ 20°C	kPa	0.106
Vapour Density @ 20°C	(air = 1)	5.4
Explosive Limits in Air	%	0.7 - 5.4
Viscosity	cSt	Not available
Volatiles	%vol/vol	100
Autoignition Temperature	°C	365
Solubility in Water	% w/w	Negligible

The values listed are indicative of this product's physical and chemical properties.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature and pressure. **Conditions to avoid:** Sources of heat and ignition, open flames.

Hazardous decomposition products: No decomposition products except on burning.

See "Fire Fighting Measures" and "Hazardous Reactions".

Hazardous reactions: Strong Oxidizing agents

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

Will irritate throat, trachea and respiratory tract. Ingestion of small amounts may cause nausea. Ingestion of large amounts will have a narcotic effect; headaches, dizziness, euphoria, loss of appetite and possible unconsciousness. Aspiration into the lungs by ingestion or vomiting may result in chemical pneumonitis.

Product: ISOPAR H Date of Issue: 13th April 2023

Page 5 of 8





2/20 Trugood Drive East Tamaki Auckland PO Box 258 031 Botany Manukau 2163

Eve Contact

This product may be moderately to severely irritating to eyes and may result in corneal damage if not promptly treated. Exposure to vapour concentrations of 500 – 1000 ppm usually is irritating to eyes.

Skin Contact

This product is mildly irritating to skin with short term contact. Prolonged or repeated exposure will increase risk of dryness and cracking of skin.

Inhalation

Vapour concentrations above 500 ppm are irritating to nose and throat. Exposure to high concentrations (above 1000 ppm) result in narcotic effects; possible symptoms are headaches, dizziness, loss of co-ordination, nausea, loss of appetite. In severe case loss of unconsciousness is possible.

Chronic Effects

No Specific information available

Other Health Effects Information:

Exposure to this product can increase toxicity to kidneys and liver to hydrocarbon solvents such as trichloroethylene and chloroform.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity: Product is identified as being toxic to aquatic life with long-lasting effects. **Persistence/degradability:** Product contains components that do not rapidly biodegrade. Not expected to

significantly bioaccumulate.

Mobility: This product is highly volatile and will rapidly evaporate to air if released into

water. Expected to leach readily in most soil types.

Other information: None

Environmental Exposure Standards: Not set.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

Special Precautions for Landfill or Incineration:

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

Product: ISOPAR H Date of Issue: 13th April 2023

Page 6 of 8





2/20 Trugood Drive **East Tamaki** Auckland PO Box 258 031 **Botany** Manukau 2163

14. TRANSPORT INFORMATION

UN Number:

Shipping name: HYDROCARBONS LIQUID, N.O.S.(NAPHTHA PETROLEUM HYDROTREATED HEAVY)

Class: 3 Packing group: Ш Hazchem code: 3YE

Dangerous Goods Segregation

This product is classified as Dangerous Goods Class 3, Packing Group II. Please consult NZS 5433:2012 Transport of Dangerous Goods on Land for information.



15. REGULATORY INFORMATION

Country/ Region: New Zealand Inventory: AICS, NZIoC Status: Components listed

EPA New Zealand HSNO Approval Code: HSR002650, Solvent (Flammable) Group Standard 2006; Refer www.epa.govt.nz for information on Controls.

16. OTHER INFORMATION

Issue number:

Date of Issue: 13th of April 2023 Reasons for Issue: New Safety Data Sheet.

Replaces:

Abbreviations:

AICS: Australian Inventory of Chemical Substances CAS

Number: Chemical Abstracts Number **Environmental Protection Authority** EPA:

IARC: International Agency for Research on Cancer National Institute of Occupational Safety & Health NIOSH: National Occupational Health and Safety Council NOHSC:

New Zealand Inventory of Chemicals NZIoC: **Recommended Exposure Limits** REL:

Short Term Exposure Limit (15 minute exposure period) **STEL** TWA Time-Weighted Average (8 hours exposure period)

ISOPAR H Product: 13th April 2023 Date of Issue:

Page 7 of 8





2/20 Trugood Drive **East Tamaki** Auckland PO Box 258 031 **Botany** Manukau 2163

References:

Supplier Material Safety Data Sheets EPA website: www.epa.govt.nz

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact TMK Packers Ltd.

END OF SAFETY DATA SHEET

Product: ISOPAR H 13th April 2023 Date of Issue:

